

DESI-LED-SPECS

Fil direct $\rightarrow 3,2 \Omega$
à souder

Actual.

LED	LED model	R_min (Ohm) (soudé)	Potentiomètre (soudé)
D01	GW JCLMS1.EC-GUHQ-5H7I-1	33,9	30
D02	RLCU-355	75,7	75
D03	RLCU-365	75,5	75
D04	UVLED365E-SMD	75,6	75
D05	RLCU-375	91,3	90
D06	APG2C1-375-E	53,0	30
D07	RLCU-380	118,7	90
D08	SMC395	88,4	61
D09	RLCU-400	144,3	100
D10	SMC405	84,5 Ω	75
D11	RLCU-410	262,4 Ω	100
D12	SMC415	171,6	69
D13	SMC430	262,5	63
D14	LD-W5AM-1U4U-35	313,4	43
D15	LB-W5SM-FZHX-35	515,0	51
D16	SMC470	273,0	82
D17	598-8191-107F	142,0	90
D18	SMC490	62,18	63
D19	1 slot type RLCU-XXX		
D20	1 slot type RLCU-XXX		
D21	LV-W5AM-JZKZ-25	810 Ω	40
D22	598-8181-107F	163,1 Ω	100
D23	SMC525	1,213 $k\Omega$	82
D24	LT-W5SM-JYKY-25	877 Ω	40
D25	LTQ39G-Q1S2-25-1	250,1	243
D26	GT PSLM31.13-GUHQ-26-MP	475,0	40
D27	SMC565	1206 $k\Omega$	90
D28	SMT570	1,225 $k\Omega$	163
D29	SM1204SGC	130,3	130
D30	598-8150-107F	149,5	150
D31	SM1204UYC	130,9	130
D32	598-8140-107F	149,9	150
D33	LY-W5SM-HZJZ-46	437,3	63
D34	598-8130-107F	156,3	150
D35	LA-W5SM-JYKY-24	0,976 $k\Omega$	63
D36	SM1204UOC	189,4 Ω	130
D37	598-8120-107F	157,0	150
D38	SMC630	0,853 $k\Omega$	100
D39	598-8110-107F	150,5	150
D40	1 slot type SMC-XXX		
D41	SMC660N	173,5	100
D42	SMC680	110,4	110
D43	SMT700	110,2	110
D44	SMC720	1,256 $k\Omega$	110
D45	SMC735	68,3	69
D46	APG2C1-740	309,7	69
D47	SMC750	204,3	63
D48	SMC770	62,5	63
D49	SMC780	35,8	69
D50	SMC810	68,3	69
D51	SMC830	68,4	69
D52	SMT850N	68,5	69
D53	SMC870	68,4	69
D54	SMC890	68,7	69
D55	SMC910	68,7	69
D56	SMC940	68,7	69
D57	SMC970	68,6	69
D58	SMC1050		69
D59	1 slot type SMC-XXX		
D60	1 slot type SMC-XXX		

33,9 Ω
75,7